

Diamond Gutter Shield Pro™

DIAMOND Gutter Shield Pro™



White



Weatherwood

Description	White	Weatherwood
5 inch x 48 inch	85400BX	85419BX
6 inch x 48 inch	86400BX	86419BX

Distributed by:



BERGER

Quality Building Products Since 1874



a Euramax® company

BERGER BUILDING PRODUCTS, INC.
805 Pennsylvania Blvd. • Feasterville, PA 19053

(800) 523-8852

(215) 355-1200 • FAX: (215) 355-7738

For more information on the Diamond Gutter Shield Pro visit

DiamondGutterShield.com

©2011 Berger Building Products, Inc. Printed in USA 0411

Put a Stop to Clogged Gutters - Forever!

BERGER

Quality Building Products Since 1874


DIAMOND Gutter Shield Pro™

Features:

- ◆ 4 foot sections provide fast installation for the contractor
- ◆ Pressure fit design ensures a snug fit every time
- ◆ Can be installed with any asphalt, tile or metal roof system
- ◆ Drip lip reduces tiger striping
- ◆ Tested to handle the heaviest of rainfall - up to 40" per hour
- ◆ Aluminum with high impact powder coat finish reduces scratching and cracking
- ◆ Available in White and Weatherwood
- ◆ Available for 5" and 6" K style gutters
- ◆ Sold only in pro-packs – 25 pieces per carton

Benefits:

- ◆ Installs on new or existing gutters
- ◆ Helps prevent clogs and overflowing
- ◆ Keeps leaves, needles, and debris out of gutters
- ◆ Prevents animals, birds & insects from nesting
- ◆ Helps prevent cracked foundations, wet basements and landscape erosion



US Patent Pending

Installation Instructions:

1. Check gutter system is clean and in good repair.
2. On first section of Diamond Gutter Shield Pro, create a 2" end flap by notching (2a) and bending (2b).
3. Install Diamond Gutter Shield Pro, overlapping the 1/2" notched end with the straight end of previous section.
4. Engage each piece into the back of gutter hangers (4a) and front lip of gutter (4b).
5. Use miter cuts to cover any corners in gutter system.
6. Optional - For added security, install a 1/2" galvanized zip screw through face of shield, into front lip of gutter.
7. On the last section, create a 2" end flap, as in step 2.

Go to DiamondGutterShield.com for detailed installation instructions.

